




Illustration image

## RECOMMENDED ACCESSORIES

- TOOL BOX HBC
- IRON SEPERATOR
- H-Lock QUICK COUPLING SYSTEM
- CRUSH CONTROL
- DUST SUPPRESSION
- ROTATION METER
- BUCKET TEETH

## HARTL CRUSHER Performance\*



\* The production capacities vary based on material, feed size and close side setting. Indicated capacities based on medium hard material crushed under optimal conditions and taking the swivel time into account.

- HBC 650
- HBC 750
- HBC 950
- HBC 1250

MODEL	HBC 750
Excavator weight lbs**	≥ 39,700
Inlet opening in	30 x 20
Rotation rpm	350
Rated capacity acc. ISO 7451 y³	0.95
Hydraulic motor cc	80
Max. sound power level dB(A)	L <sub>W,A</sub> 110.5
Oil flow rate US gpm	> 39
Oil pressure psi	3190
CSS toggle STD/OPT in	1.37-4.00/0.48-2.95
Toggle system	Up-thrust
Mainframe construction	HARDOX 450
Crushing unit	Cast iron
Greasing system	Central 1-point
IN/OUT acc. ISO 6162 (SAE J518c)	3/4" 6000 psi flange
DRAIN acc. ISO 6162 (SAE J518c)	1/2" 3000 psi flange
Length in	87.00
Width in	47.63
Height in	53.93
Weight lbs	6,180
Operation temperature °F	14 - 140
HS Code	84742000
Warranty months	12

Right to alter technical information without notice reserved

\*\* Always consult and obey your machines lifting capability guidelines to insure safe operation of the crusher.